


Pet Food Machinery and Solutions by

scansteel[®] foodtech



scansteel foodtech A/S is among the leading companies globally in designing, engineering, manufacturing, installing, and servicing single machines and equipment as well as complete preparation processing lines for the global wet and dry pet food industries. Our core pet food industry competences are within the meat and bone raw material preparation segment, such as, but not limited to, whole pallet crushers, grinders for fresh and frozen meat and bone raw material, mixers, vacuum mixers, pumps for all applications, pump and hopper fed emulsifiers, batching and weighing stations, and silo systems for all types of Heavy Duty pet food applications.

scansteel foodtech A/S' portfolio of standard pet food preparation machines and equipment comprises a total of approx. 140 standard machines and equipment.

In addition to our standard range of pet food preparation machines and equipment, scansteel foodtech A/S develops individually tailor-made machines and equipment in co-operation with our customers.

Our pet food preparation processing lines can be delivered with or without Line Control Systems, with or without recipe formulation software for uploading of data to customers' existing ERP systems and MCC's.

scansteel foodtech A/S is a 100% privately owned Danish company (Scandinavia). scansteel foodtech A/S resides in the former 10,450 m² Wolfking® domicile in the city of Slagelse 1 hour from Copenhagen Airport.

Feel free to contact scansteel foodtech A/S for a mutual conversation concerning any present or future pet food preparation processing requirements you may have.



Table of Contents

Introduction	2
Pet Food Industry Products	5-6
Whole Pallet Crushers/Pre-breakers	7
Whole Pallet Crusher	7-11
Block Crusher	12
Cut the Top	13
Grinders - Single Worm	14
MG 200	15
MG 225 Frozen Block Grinder	16
MG 250	17
MG 330	18
MG 400 & MG 400 Heavy Duty	19-20
SuperGrind 400/260	21-22
SuperGrind 550/310 Super Heavy Duty, Brutalis	23
Grinders - Double Worm	25-28
Mixers	29-34
Defrosting	35-36
Pumps	37
SuperPump	37-40
ContiPump	41-43
Twin Shaft Feeder	44
Emulsifiers – Overview	45
scanEmul 175 - Hopper fed	46
scanEmul 175 - Screw hopper fed	47
scanEmul 175 - Pump fed	48

Danish quality
equipment conceived,
engineered, and
manufactured in
Denmark

Table of Contents

QuadroCut 225	49
QuadrocutVac 225	50
QuadroCut Vac 225- TemBi	51-52
Heavy Duty Emulsifiers	53
MC 250 & MC 300	53-56
Pre-Emulsifier	57
PE 400 & PE 550	57
Meat-bone Separators/Deboners/Desinewers	58
Gravy Production Systems	59
scanGravy with Ytron Powder Dispenser - Heavy Duty Applications	59
scanGravy with Venturi System	60
Storage & Batching	61
Silo Systems	61-62
Swing Loader Systems	63-65
Product Transfer Equipment	66
Infeed Systems for Grinders - Frozen Blocks	66-67
Infeed Systems for Grinders - Fresh Raw Meat Materials	68-69
Discharge Systems for Grinders	70-71
Screw Conveyors	72-73
scanGiraff.	74-76
scanLift	77-80
scanSwing	83
Line Control System	84
Layout	85-88
Global Team	89

Pet Food Industry Products

scansteel foodtech A/S specializes in machinery, equipment, and complete processing lines.

A Dry Pet Food - Slurry for real meat addition



B Paté



C Filets



D

Chunks in Gravy or Jelly



E

Dog Rolls



E

BARF (Biologically Appropriate Raw Food)



Whole Pallet Crushers/Breakers

WPC 2000-SINGLE & WPC 2000-TWIN

The scansteel foodtech® Whole Pallet Crusher, WPC, range is probably among the most comprehensive ranges available. The entire cabinet and frame structure is manufactured in stainless steel AISI 304. The WPC is available with single or double rotary claw shafts. The infeed width is available in either 1500 mm or 2000 mm. The Heavy Duty design is performed with main bearing positioned on each side of the claw shaft ends thus eliminating all axial forces between the claws and gear box



Whole Pallet Crushers/Breakers

WPC 2000-SINGLE & WPC 2000-TWIN



Bottom picture : Please note the shock absorbers which allow the WPC to remain stable (not moving) even when the WPC is fed by a fork lift truck dumping whole pallets into the crusher cabinet.




Top picture: Heavy Duty safety clutch claw and gear box.

Bottom picture: The rotary and stationary claw design comes in two versions.

SET OF STATIONARY CLAWS

Fixed onto the cabinet as counter claws to the rotary claw shaft. Each stationary claw is welded onto both sides of the rotary claw shaft.

Available Dimensions of Claw(s):	A	B
Thickness of rotary claw(s), on claw tip	65 mm	45 mm
Thickness of rotary claw(s)	60 mm	40 mm
Distance between stationary claw(s)	80 mm	



Whole Pallet Crushers/Breakers

WPC 2000-SINGLE & WPC 2000-TWIN

scansteel foodtech A/S manufactures a range of Whole Pallet Crushers with either single claw or double claws with a standard infeed width of 2000 mm. A Whole Pallet Crusher is capable of crushing a pallet full of frozen together blocks which as such appear as one entire frozen block of, example only, 1200 x 800 x 1500 mm.



Heavy Duty bearings – on each end of the crusher claw(s). Absorbing/eliminating all axial forces between claw(s) and gear box.

The entire infeed hopper is manufactured in 20 mm stainless steel plate AISI 304.

scansteel foodtech® Whole Pallet Crusher, WPC 2000-Single, is shown on picture below.

FEATURES:


- Constructed in 20 mm stainless steel plate AISI 304.
- Infeed hopper and discharge frame/hopper manufactured according to customer requirements/demands.
- Crusher claw(s) made of hardened material.
- Designed with few spare and wear parts leading to very low operation and maintenance costs for the machine.
- Frozen block dimensions: 1000 x 1000 x 1000 mm.
- WPC 2000-Single, 10,000 – 20,000 kg/hour (22,000 – 44,000 lbs./hour. Power/motor 37 / 45 / 55 / 75 kW
- WPC 2000-Twin, 20,000 – 60,000 kg/hour (44,000 – 130,000 lbs./hour). Power/motor 37 / 45 / 55 / 75 kW – 2 x 110 kW.
- Bearing on each end of crusher claw(s).



Whole Pallet Crushers/Breakers



Crusher claw(s) made of mild steel with hard ended claw tips.



Planetary gear box assembly. Between gear box and crusher claw, a Heavy Duty clutch system prevents damage to the gear box in case a large foreign (metal) object by mistake is thrown into the Whole Pallet Crusher.



scansteel foodtech® Whole Pallet Crusher, WPC 2000-Single, shown in application where existing footprint is sparse and where the pre-broken frozen blocks must be elevated to approx. 5000 mm.

Below: Picture shows the 2000 mm wide inlet/ infeed hopper. The hopper is typically loaded by a fork lift truck, a lifting device, or an inclined belt conveyor.



Final installation of Whole Pallet Crusher, WPC 2000-Single, at customer site, shown with platform with ladder.



Horizontal screw shown with closed lid.


Whole Pallet Crushers/Breakers

scansteel®
foodtech



Whole Pallet Crusher, WPC 2000 perfectly integrates with complete pet food processing lines. WPC 2000 shown with a scansteel foodtech® inclined screw conveyor with built-in buffer capacity for a crushed whole pallet of meat raw materials.

The claws for the WPC 2000 can optionally be delivered with claws of mirror polished stainless steel.



Buffer hopper with mounted weighing cells for batch control and automatic start/stop of machinery.



View of the belt transmission.



Top view looking at the inside/infeed section where the whole pallets of meat raw material will be fed into the WPC 2000.


Block Crusher

SCANSTEEL FOODTECH® SCANSTRUCTOR

The scansteel foodtech® scanStructor is a Heavy Duty block crusher for crushing of individual frozen meat raw material blocks. Typical application is that the scanStructor is fed by individual frozen blocks.



Front view of the
scanStructor.
Outlet Ø600 mm.



The scanStructor is typically equipped with a 37 kw motor.



scansteel foodtech® scanStructor top view, showing the infeed
hopper with heavy duty crushing claws.



Showing rear left view with hygienic zone.

Cut the Top

The scansteel foodtech® Cut the Top is the machine technology to use for breaking off layer by layer of whole pallets of frozen together blocks. The Cut the Top is designed to cut out one single layer of frozen blocks at a time from a complete pallet consisting of frozen together blocks. You can choose both manual and automatic mode. Includes manual layer adjustment option for the operator.



Rear view showing how the frozen pallets are loaded into the Cut the top.



Close up view showing control of continuous discharge or discharge on-demand.



GRINDERS – SINGLE WORM

Over the years, the scansteel foodtech Group has conquered the position as THE supplier with the world's widest and most comprehensive grinder programme. scansteel foodtech A/S delivers, among others, the following grinder programme:

- Cabinet Grinders ranging from Ø200 mm – Ø550 mm (Ø8" – Ø22") – 22 kW – 200 kW (type name: MG).
- Open Cabinet Grinders ranging from Ø200 mm – Ø550 mm (Ø8" – Ø22") – 22 kW – 200 kW (type name: MG Low).
- SuperGrind series ranging from Ø400 mm – Ø550 mm.



SINGLE WORM/AUGER GRINDERS:

SuperGrind SG 550/310 Super Heavy Duty, Brutalis	160 - 250 kW
SuperGrind SG 400/260	110 - 160 kW
MG 400 Super Heavy Duty, Brutalis	160 - 200 kW
MG 400 Heavy Duty	132 - 160 kW
MG 400	90 - 110 kW
MG 330	75 - 90 kW
MG 250	55 kW
MG 225	37-45 kW
MG 200	30 kW

FEATURES:

- Constructed in stainless steel AISI 304.
- Grinders from Ø200 mm – Ø550 mm.
- Grinding capacities from 2000 – 40,000 kg/hour.
- Large hopper infeed area preventing bridge building.
- Low noise level.
- Low energy consumption.
- 75 kW – 250 kW motor.
- 1 or 2 units dismantling crane.
- Heavy Duty construction.

Grinders

GRINDER – SINGLE WORM: MG 200


The scansteel foodtech® MG 200 & MG 250 grinders are specially designed for fresh meat and fresh meat raw materials as well as for pre-broken/crushed frozen blocks.




Infeed hopper secured by trip wire. When safety devices have been triggered, they will stop the machine after maximum of 4 (four) seconds.



MG 200 shown with back panel open. All stainless steel construction, including bottom frame.



*Top picture: Safety guard for platform shown in running position.
Bottom picture: Safety guard for platform shown in open/cleaning/inspection position.*



Stirring/feeding device. To secure continuous infeed of difficult/sticky meat raw material at the grinder worm/auger.

GRINDER – SINGLE WORM: MG 225 - FOR FRESH RAW MATERIAL AND FROZEN BLOCKS

The scansteel foodtech® MG 225 Frozen Block Grinder is incredibly strong despite its compact size and it combines efficient processing with quality grinding. The MG 225 is specifically designed to grind whole frozen blocks and is perfect for grinding of fresh meat raw material as well. The MG 225 Frozen Block Grinder is equipped with a 45 kW motor, and it maintains a low operating cost and a low energy consumption for daily production. But without compromising on scansteel foodtech's well-known high quality standards, such as high hygienic design, operating safety, and performance.



The scansteel foodtech®
MG 225 Frozen Block Grinder



Operator panel



Top view of infeed hopper of the MG 225




Accessory/cleaning trolley with space for all
loose grinder parts.




The scansteel foodtech® MG 225 is designed to be fed by either a belt conveyor or a lifting,
here shown being fed by the scanLift SC 350 with 220 L trolley.

Grinders


GRINDER – SINGLE WORM: MG 250



Top picture: Assembly of SINGLE knife set including grinding worm/auger.
Bottom picture: Assembly of DOUBLE knife set including grinding worm/auger.



Accessory/cleaning trolley with space for all loose grinder parts.



A prime example of scansteel foodtech® hygienic design is given by the hygienic zone positioned between the worm/auger and the gear box. Hygienic zone shown in running position (closed) and in cleaning/inspection position. When opened, the grinder cannot be started until the guard has been positioned in closed position.



Grinders


GRINDER – SINGLE WORM MG 330

The scansteel foodtech® MG 330 is equipped with either 75 kW or 90 kW electrical motor depending on specific grinding application(s). The MG 330 grinder is incredibly strong and reliable for both frozen blocks of meat raw material of any type as well as for certain bone-in products plus fresh meat raw materials. It comes with either a fixed or a loose pre-cutter depending on the grinding application.



Infeed hopper shown from top view. Please note the grinding worm/auger with the sharp knife edge, designed to grab and feed both frozen blocks and fresh meat raw materials.

MG 330 shown with standard operator panel with MINIMAL electrical/ electronic parts. Please note the safety guard is in open/disassembly position.



MG 330 shown with optional flange mounted extension infeed hopper and trip wire.

MG 330 shown in mounting position. The cleaning trolley for worm/auger shows/ indicates how to dismount the worm/auger, while avoiding heavy lifts/pulls.

Grinders

GRINDER – SINGLE WORM: MG 400 & MG 400 HEAVY DUTY

The scansteel foodtech® MG 400 & MG 400 Heavy Duty grinders are incredibly strong and reliable grinders for both frozen blocks of meat raw material of any type as well as for certain bone-in products plus fresh meat raw material. They come with either a fixed or a loose pre-cutter depending on the grinding application.



MG 400 Heavy Duty shown in disassembled position and with all loose parts positioned on accessory/ cleaning trolley for inspection and cleaning prior to assembly.




Infeed hopper shown from top view.



Hygienic zone shown in 3 (three) positions: running position (closed) and cleaning position shown from both angles.

scansteel foodtech® MG 400 Standard LOW and MG 400 Heavy Duty LOW. Grinder without cabinet. Shown with scansteel foodtech® hydraulic knife tensioning system.



Grinders

GRINDERS – SINGLE WORM: MG 400 & MG 400 HEAVY DUTY




Optional Extra, Example Only:
scansteel foodtech® worm/auger.


Please note: Worm/auger is not included in the price of cleaning trolley for worm/auger.



Cleaning trolley for worm/auger shown without worm/auger.



Cleaning trolley for worm/auger shown after the worm/auger has been removed from grinder.



Cleaning trolley for worm/auger shown with safety shaft mounted for cleaning, inspection, and transport.



MG 400 worm/auger.



Heavy Duty designed worm/auger with sharp knife edge on hopper part of worm/auger to grab frozen blocks.




scansteel foodtech® accessory/cleaning trolley shown with all loose parts for inspection and cleaning.



Grinders

SUPERGRIND SG 400/260



Worm/auger shown mounted in the SuperGrind 400/260 cabinet, top view.




SuperGrind 400/260 shown fully assembled, ready for production. Shown with safety inlet cage which prevents meat raw material, such as frozen blocks, from being ejected during feeding of the grinder.



SuperGrind 400/260 shown with all side panels dismantled, side view. Designed for easy access at maintenance and inspection. The automatic greasing system for main bearing and front bearing is also shown.


SuperGrind 400/260 shown with all side panels dismantled, rear view. Visualizes perfectly the design with easy access for maintenance and inspection.



Globally, the scansteel foodtech® SuperGrind 400/260 & 550/310 are probably the toughest and most Heavy Duty “Work Horses” among meat raw material grinders. Designed specifically for global pet food and rendering industries for grinding of:

- Entire beef bones - all types including femur bones.
- Entire pork bones - all types including femur bones.
- Poultry bones – all types.
- Fish bones – all types.
- Pre-broken bones.
- Soft meat raw material.

The Heavy Duty design of worm/auger for SuperGrind 400/260



Grinders

SUPERGRIND SG 400/260



Cabinet without worm/auger showing the flights of the lining.



Front end of SuperGrind 400/260 shown disassembled, with worm/auger in place, ready for mounting of 3-bladed cut-knife. Cut-knife recessed into the worm/auger.



Front end of SuperGrind 400/260 shown with worm/auger and 3-bladed cut-knife assembled.



SuperGrind 400/260 with knife set and front end fully assembled. Automatic greasing of front end bearing is shown as well.



The SuperGrind 400/260 equipped with 90 kW - 160 kW motor. The SuperGrind 400/260 can be equipped with single or double knife set.



Worm/auger trolley.



Cleaning trolley.

SUPERGRIND SG 550/310 SUPER HEAVY DUTY, BRUTALIS

The SuperGrind 550/310 is equipped from 160 - 250 kW motor and with single or double knife set. The scansteel foodtech® SuperGrind 550/310 is within its size/capacity probably the TOUGHEST and most Heavy Duty "Work Horse" among ALL meat raw material bone grinders. The SuperGrind SG 550/310 is designed specifically for global pet food industry for grinding of:

- Entire beef bones – all types including femur bones.
- Entire pork bones – all types including femur bones.
- Poultry bones – all types.
- Fresh/Frozen pork – all types.
- Fish bones – all types.
- Pre-broken bones.
- Soft meat raw material.




Top view of
Supergrind 550/310



Grinders



- SuperGrind 550/310 worm/auger.



- SuperGrind 400/260 worm/auger.




- MG 400 worm/auger.



- CG 300 grinding worm/auger.



- CG 300 feeding/breaking worm/auger.



- CG 400 shark tooth worm/auger

For more information, please contact us!

Grinders - Double Worm

DOUBLE WORM COMBIGRIND CG 225 / CG 300 / CG 300 HEAVY DUTY / CG 400 – THE BEAST

These truly unique and universal grinders provide first-class grinding results, fully comparable with and even surpassing those of conventionally specialised grinders for fresh, tempered, or deep-frozen blocks without changing anything but the incoming raw material to be ground, coarsely or finely, as required. scansteel foodtech® CombiGrind Grinders from Ø160 mm – Ø400 mm (type name: CG).


CombiGrind CG 400
– The Beast



DOUBLE WORM/AUGER GRINDERS:


CombiGrind 400 Heavy Duty, The Beast	22 + 110 - 200 kW
CombiGrind 330 Heavy Duty	22 + 110 - 132 kW
CombiGrind 300 Heavy Duty	22 + 90 - 132 kW
CombiGrind 300	22 + 90 kW
CombiGrind 225	15 + 75 kW

High performance grinding within a wide capacity range is achieved through a low-tolerance, rigid design with smoothly shaped worms, hand-forged, welded, and ground superfinely by skilled Danish craftsmen combined with the smooth surfaces of a high precision CNC milling lining.



Grinders

DOUBLE WORM COMBIGRIND CG 225 / CG 300 / CG 300 HEAVY DUTY / CG 400 – THE BEAST



HYGIENIC ZONE

A prime example of scansteel foodtech[®] hygienic design is given by the two hygienic zones – one positioned between each of the worms/augers and one between the gear boxes.

Top picture: Details of the two unique hygienic zones for both top/feeding worm and bottom/grinding worm. This unique feature physically prevents cross contamination. Protected by safety grill and safety switch, which will stop the motor in three to four seconds from activation to full stop.



The electrical panel is embedded into the machine cabinet. The electrical panel can swing away to grant full access to the interior of the machine at maintenance, etc.

Grinders

COMBIGRIND CG 225 / CG 300 / CG 300 HEAVY DUTY / CG 400 – THE BEAST

CombiGrind CG 300 shown with automatic start/stop of grinder by level sensors built into front legs. CombiGrind CG 300 shown with 300 L extension hopper, which will be designed according to customer request and to be quoted separately.



Fresh soft meats as well as tempered or hard frozen blocks are efficiently processed jointly or separately without changing any mechanical components due to the ingenious design of hopper, transfer area between the worms/augers combined with efficient fixation of the frozen blocks. Narrow tolerances eliminate backwash, fines, or smearing.



Operator control with easy-to-understand push button operation of start, stop, and emergency. Pre-setting of worm/auger speeds and programming functions with logically designed graphics on the touch panel. Programmes with fixed settings for various products can be keyed in with password protection. The scansteel® scanControl function can be set to optimize the feeding worm/auger speed in relation to the grinding worm/auger, thus reducing grinding capacity flow fluctuations.

COMBIGRIND CG 225 / CG 300 / CG 300 HEAVY DUTY / CG 400 – THE BEAST



Removal of breaker worm/auger and grinding worm/auger. CombiGrind CG 400 – The Beast

Easy and efficient cleaning of both feeding worm/auger and grinding worm/auger, which can both be easily disassembled and removed together with other grinding tools by means of the included tool trolleys. Hole plates are easily removed and replaced during production with the included extraction tool, fitting the inner thread in the hole plate centre hole. The hygienic design provides easy access to and cleaning of all surfaces in contact with the product. The product area and drive components such as bearing etc. are completely separated by wide flushing channels with full visibility of and access to bearing sealings and drive clutches. This provides complete food safety as it is impossible for lubricants or bearing impurities to enter the product zone. Foldable safety fences prevent access to rotating parts during operation. All surfaces are either smoothly polished or ground and glass bead peened.



Removal of breaker worm/auger for CombiGrind CG 225, CG 300, CG 300 Heavy Duty.

MIXERS FROM 200 L - 12,000 L

scansteel foodtech® Twin Shaft Mixer, TSM(V) positioning on rack extension.



scansteel foodtech® Twin Shaft Mixer, TSM(V) positioning on floor.



Inside view of scansteel foodtech® Twin Shaft Mixer, TSM(V)

MIXERS: Side-by-side, TSM(V)	
Twin Shaft Mixers	TSM - From 250 Litres – 12.000 Litres
Twin Shaft Mixers Vacuum	TSMV – From 250 Litres – 12.000 Litres
MIXERS: Intermeshing TSMI(V)	
Twin Shaft Mixers	TSM - From 200 Litres – 12.000 Litres
Twin Shaft Mixers Vacuum	TSMV – From 200 Litres – 12.000 Litres
MIXERS: Single, SSM(V)	
Single Shaft Mixers	SSM - From 250 Litres – 12.000 Litres
Single Shaft Mixers Vacuum	SSMV – From 250 Litres – 12.000 Litres

Mixers

MIXERS FROM 200 L - 12,000 L



scansteel foodtech® Twin Shaft Mixer, TSM(V) shown with back panel open, view of motors.



Close up view of load cells.




Close up view of operator panel with two hand JOG function for cleaning and inspection.




scansteel foodtech® Twin Shaft Mixer discharge gate system.

OPTIONAL EXTRAS: MIXER WING TYPES



Paddle wings.





Spiral mixing wings.




Paddle mixing wings, special application.

Mixers

CO₂ / N₂ COOLING SYSTEM




scansteel foodtech® Valves System and manifold. Each valve is equipped with a solenoid valve for individual control of each valve. (scansteel foodtech® CO₂ / N₂ Cooling System pictured to the right)



scansteel foodtech® Valves System seen from the inside of the mixer.



Valve shown mounted on mixer. Temperature sensor shown to the left and valve shown to the right.



Ultra hygienic valve mounting/dismounting design. Easy to clean and inspect.

STEAM INJECT SYSTEM



Close up of scansteel foodtech® Bottom steam injection system shown on Twin Shaft Mixer, TSM(V)



Number of steam nozzles depending on mixer size.


MIXERS: Side by side, TSM(V)

Twin Shaft Mixers:

TSM - From 250 litres - 6250 litres

TwinShaft Mixers Vacuum:

TSMV - From 250 litres - 6250 litres



Left wing	Right wing	Wing rotation options for TSM(V) Series
		Left wing clockwise – Right wing clockwise
		Left wing counter clockwise – Right wing counter clockwise
		Left wing clockwise – Right wing counter clockwise
		Left wing counter clockwise – Right wing clockwise


MIXERS: Intermeshing TSMI(V)

Twin Shaft Mixers, Intermeshing:

TSMI - From 200 litres - 12,000 litres

Twin Shaft Mixers, Intermeshing Vacuum:

TSMIV - From 200 litres - 12,000 litres



Left wing	Right wing	Wing rotation options for TSMI(V) Series
		Left wing clockwise – Right wing counter clockwise
		Left wing counter clockwise – Right wing clockwise


MIXERS: Single, SSM(V)

Single Shaft Mixers:

SSM - From 250 litres - 12,000 litres

Single Shaft Mixers Vacuum:

SSMV - From 250 litres - 12,000 litres



Left wing	Wing rotation options for SSMV) Series
	Left wing clockwise – Right wing clockwise
	Left wing counter clockwise – Right wing counter clockwise

Features and Optional Extras

FEATURES:

- Constructed in stainless steel AISI 304.
- Safety equipment for CE conformity.
- Low energy consumption.
- Ideal for frozen meat and fresh/frozen mixtures. A flexible and high-performance mixing is given with both a high peripheral wing speed and a gentle handling of the mentioned raw materials.
- Minimum product residues and cross-mixing of batches, also including fully separated and sealed hygienic zone preventing any possible cross contamination.
- Various lid configurations: rear or side hinged. Optional as pneumatically operated.
- Computerized design of mixing wings and mixer geometry combined with the programmable mixing action ensures optimum processing results for you.
- Low noise level.
- Mixer controls available in range from ordinary push button operated versions to advanced PLC controlled systems. All PLC systems are supplied with reliable and easy accessible finger-touch operator panel with digital read-out of all mixer functions. Make Allen Bradley.


Features and Optional Extras

OPTIONAL EXTRAS:

- Dust lid without sealing
- Grill lid.
- Plate lid with sealing.
- Weighing system on frame.
- Weighing system, floor mounted.
- Frame prepared for weighing system.
- Temperature sensor (incl. in CO₂ and steam) – PT100.
- CO₂ top injection system with snow horns incl. control and lid.
- CO₂ bottom injection system.
- N₂ top injection system.
- N₂ bottom injection system.
- Steam bottom injection system incl. nozzles.
- Water dosing system, automatic.
- Double jacket for heating/cooling and insulation (not pressurized).
- Polished mixing container inside meat product zone.
- Interlock for trolleys - photo cell.
- Inspection platform, various executions.
- Mixing wings optional as standard paddle or spiral wings. Standard and paddle wings to run either side-by-side or intermeshing.

SCANDEFROST SDV FROM 6000 L - 12,000 L - WITH VACUUM & BOTTOM DIRECT STEAM INJECTION

How to defreeze pre-ground or crushed frozen meat- and poultry blocks as well as frozen blocks of bones in minutes (NOT hours!) Frozen blocks directly from the freezer down to minus 30°C, before pre-grinding/crushing is not a problem with the scansteel foodtech[®] vacuum defrosting method and scanDefrost technology.



View of scansteel foodtech[®] scanDefrost nozzles / manifold system.



The scansteel foodtech[®] scanDefrost series has made production logistics much easier, as the meat raw materials to be further processed is taken directly from the freezer without time consuming storage in tempering rooms or other thawing facilities.

The Method:

The scansteel foodtech[®] vacuum defrosting method provides defrosting of pre-crushed, frozen blocks of meat within minutes.

Main advantages:


- NO driploss
- The method is gentle to the meat and does not cause any denaturation.
- Does not cause any discoloration.
- All the valuable binding properties of the meat are maintained.

The Benefits in General:

- Simple logistics and production planning due to processing directly from the freezer.
- Substantial savings in time, floor space, and energy.
- Better yield, no drip loss, no evaporation.



Frozen cow udder product before defreezing.



Cow udder product after defreezing.




Cow udder product discharged from the scanDefrost.

Defrosting

SCANDEFROST SDV FROM 6000 L - 12,000 L - WITH VACUUM & BOTTOM DIRECT STEAM INJECTION

The Benefits with Specially Formed Products:

- Substantial energy- AND costs savings by avoiding defrosting completely.
- No need for CO₂ or LN₂ cooling gas (savings of up to euro 100 per ton of meat raw material produced).
- Up to 100% increase in mixing equipment efficiency.
- Up to 50% savings in space and electrical energy.



DEFROSTING

Sizes


6000 L, 9000 L, 12,000 L

Motor sizes


37 - 55 kW



scanDefrost 6000 L.



scanDefrost 9000 L.




scanDefrost 12,000 L.

SUPERPUMPS SP 200 / SP 250 / SP 290

The scansteel foodtech® SuperPump series comprises 3 (three) different pump sizes. Correct choice of pump depends on several factors such as, but not limited to, pump capacity, material to be pumped, temperature, viscosity, and particle size – from pre-ground meat raw material to half a pork carcass. One significant feature is the double discharge outlet which dramatically minimizes (eliminates) fluctuations in pump capacity. Pump motors are designed according to pump application.

1 Infeed Buffer/Hopper Solution


Example of scansteel foodtech® SuperPump SP 2500 L silo/buffer hopper with stirring/feeding device with SuperPump SP 200.



2500 L silo/buffer hopper with stirring/feeding device. The stirring device feeds product to the centre for discharge into SuperPump SP 200.



The transmission of a SuperPump consists of individual planetary gear box and electric motor.




Pump transmission.

SUPERPUMPS SP 200 / SP 250 / SP 290

2 Infeed Buffer/Hopper Solution

Example of scansteel foodtech® SuperPump SP 290 with 300 liter infeed hopper with anti-bridging feeding device. Suited for pump applications where sparse footprint is available.



SuperPump SP 290 infeed hopper shown with rotating feeding device for feeding screw.

3 Infeed Buffer/Hopper Solution

SuperPump SP 290 with 3300 liter storage/buffer hopper.



SUPERPUMP


Motor sizes

11 - 90 kW


SUPERPUMPS SP 200 / SP 250 / SP 290

4 Infeed Hopper Solution

SuperPump SP 250 with 250 liter hopper.




*Superpump SP 250 shown below
feeding a scanDebone 150.*



SUPERPUMPS SP 200 / SP 250 / SP 290

*SuperPump solution being fed directly by frozen block grinder.
Example: blocks ground through frozen block grinder, through final hole plate from Ø6 mm to Ø30 mm according to customer request.*



SuperPump SP 290 showing double pump discharge.




Side view of SuperPump SP 290.



Pump housing.

PUMP HEAD ASSEMBLY:



Pumps


CONTIPUMP FROM 500 L – 10,000 L BUFFER HOPPER

The scansteel foodtech® ContiPump series is for less Heavy Duty applications such as, but not limited to, pet food pre-mixes being fed into an emulsifier as well as for various buffer/storage/silo applications. The buffer hopper comes in 2 (two) versions: one single feeding screw or twin (two) feeding screws, where one screw feeds/drives the ContiPump while the other prevents/limits bridge building.



*ContiPump 4000/250 Twin Screw
Shown fully assembled ready for
production. Shown with all safety
rails in position.*

*ContiPump 4000/250 Twin
Screw. The operator panel is
shown together with a level
control.*



ContiPump pump housing, hinged.



*Shown above: Close-up of pump housing and side panel for
second screw. Both designed for easy assembly/disassembly.*

CONTIPUMP FROM 500 L – 10,000 L BUFFER HOPPER



Accessory/cleaning trolley for ContiPump.



Inside view of ContiPump 4000/250 Twin Screw.
Can also be supplied with top stirring device.



The scansteel foodtech® ContiPump series has been designed in such a way that the unit can function as a stand alone pump or, as shown above, can be designed to fully be integrated as part of an integrated solution with the scansteel foodtech® ContiPump and the scansteel foodtech® mixer series. In order to secure full hygiene solutions as well as having full access to both the mixer(s) and ContiPump for inspection/maintenance. The scansteel foodtech® ContiPumps can be placed on a "rail system" which makes it fully possible for a person to separate the ContiPump and mixer. At the same time, during production, the ContiPump is secure in "running position" in such a way that the ContiPump cannot be moved.

CONTIPUMP:

Standard hopper sizes	250 - 4250 L
Gear motor for pump section	4- 11- kW
Gear motor for screw section	5,5 - 7,5 kW


Pumps

CONTIPUMP FROM 500 L – 10,000 L BUFFER HOPPER

scansteel foodtech® ContiPump series comes in many different infeed hopper designs. Below shows a ContiPump being fed by a scansteel foodtech Mixer/Grinder for pet food snack manufacturing.



Top view of the scansteel foodtech® ContiPump and Mixer/grinder.




TWIN SHAFT FEEDER


The scansteel foodtech® Twin Shaft Feeder (TSF) has been designed for very accurate dosing of meat raw materials, including slurry. The TSF is placed on load cells for accurate dosing of both very stiff and cold products as well as more liquid meat raw materials. The spiral feeding wing ensures accurate and continuous feeding of the twin screws which feed directly into any kind of pump. The twin screws are in mesh with each other to contribute to accurate dosing.



Close up view of twin screws, front view.
Another use is simply read.



Top view and inside look of the TSF. Both the twin screws
and the feeding wing is shown.



Close up view of twin screws, top view.

Emulsifiers - Overview

SCANEMUL 175

scanEmul 175 hopper fed



scanEmul 175 screw hopper fed



scanEmul 175 pump fed




QUADROCUT 225 / QUADROCUTVAC 225

Quadrocut 225



QuadrocutVac 225



QuadrocutVac 225 - TemBi



MC 250 & MC 300


MicroCutter MC 250 - Pump fed



MicroCutter MC 250 - Hopper fed



MicroCutter MC 250 - Screw hopper fed




PRE-EMULSIFIERS

PE 400



PE 500




Emulsifiers – scanEmul 175

scansteel®
foodtech

SCANEMUL 175 - HOPPER FED

The scansteel foodtech® scanEmul 175 - Hopper fed emulsifier combines efficient and simple operation with high continuous performance, long durability, and low running and maintenance costs. The scanEmul 175 knife cassette system ensures the same uniform final particle size/emulsion quality for every production run, improve the level of fineness, optimize the protein extraction and increase production capacity. It therefore meets all the requirements for quality-oriented uniform production



Emulsion from the scanEmul 175 - hopper fed.

Ultra-Flexible Knife System Set-up


The scansteel foodtech® scanEmul 175 - Hopper fed knife cassette system has been designed so it can be assembled at the workshop by trained technicians. As such, the only thing the machine operators must do is to replace the knife cassette at agreed intervals.



Knife cassette of scanEmul 175 - Hopper fed shown assembled.




Assembly of the scanEmul 175 - Hopper fed knife cassette system. Quick and easy handling.



Emulsifiers – scanEmul 175

scansteel®
foodtech

SCANEMUL 175 - SCREW HOPPER FED



Above picture shows triple knife set, loose parts when scanEmul 175 is disassembled, together with tooling for assembly/disassembly.



Emulsifiers – scanEmul 175

scansteel®
foodtech


SCANEMUL 175 - PUMP FED

On picture (to the right hand side), the scanEmul 175 is shown positioned on a sub-frame to ensure good access for mounting/dismounting of knife sets as well as for easy access at periodical maintenance.



Close-up picture of inlet and outlet temperature sensors as well as pressure transducers.

The scanEmul 175 shown below with a scansteel foodtech® ContiPump 250 with Twin Screw to avoid bridge building. Typically, the ContiPump 250 is positioned so either one or two mixers can discharge into the infeed hopper of the ContiPump 250.



Emulsifiers – QuadroCut 225


QUADROCUT 225

The scansteel foodtech® QuadroCut 225 emulsifier is the Heavy Duty “Work Horse” among emulsifiers. The scansteel foodtech® QuadroCut 225 is designed for Heavy Duty applications with heavy duty construction from the ground up. The robust frame is designed to easily withstand the forces from electrical motors from 90 kW – 200 kW. All frame and cabinet work is manufactured in stainless steel AISI 304.



QuadroCut 225.

Side view of the QuadroCut 225
without panels.



Inside view of QuadroCut 225 output shaft
from the left angle.





Inside view of QuadroCut 225 output shaft
from the right angle.

Emulsifiers – QuadroCut(Vac) 225 scansteel® foodtech

QUADROCUT VAC 225

The scansteel foodtech® QuadroCutVac 225 is the ultimate solution for production of high quality emulsion, fully inline and continuous vacuumizing for removal of air in the final emulsion. Shown with 2500 liter infed buffer hopper. The QuadroCutVac 225 is further shown with open lid showcasing the easy cleaning and inspection access for the vacuum section of the QuadroCutVac 225.



QuadroCut Vac 225.

Ultra-Flexible Knife System Set-up

The scansteel foodtech® knife set cassettes have been designed so they can be assembled at the meat or pet food processors' workshop by trained technicians. As such, the only thing the machine operators must do is to replace the knife cassette at agreed intervals.

Example: many pet food manufacturers require the final meat and bone product to have a maximum particle size of 1.0 mm or less. This can be achieved with the PentaCut 225 knife set-up.

Knife Set Combinations:

- QuadroCut 225: 4 knives – 3 hole plates
- TripleCut 225: 3 knives – 2 hole plates
- DoubleCut 225: 2 knives – 1 hole plate



Emulsifiers – QuadroCut(Vac) 225 - TemBi

QUADROCUTVAC 225 - TEMBI



QuadroCutVac 225 - Tembi




Technical Specifications for QuadroCut(Vac) 225 Series

Motor size:	Standard range: 90 kW – 200 kW.
Emulsion production capacity:	4000 – 20,000 kg/hour.
Electrical controls:	Allen Bradley operator panel and PLC. Siemens operator panel and PLC.
Emulsifier knife set speed:	Frequency controlled speed of 2200 – 3000 rpm. Typically, the most important speed control is given by the infeed pump speed which can be pre-programmed in the control panel of the emulsifiers.
Main bearing:	Oil filled bearing. Oil cooled.


Emulsifiers – QuadroCut(Vac) 225 **scansteel®** foodtech

EMULSIFIERS, QUADROCUT 225 & QUADROCUTVAC 225 - KNIFE CASSETTE ASSEMBLY


1




2




3



4



5



6



Heavy Duty Emulsifiers

MC 250 & MC 300 - HOPPER FED



View of hopper infeed of MC 300 - Hopper fed

MicroCutter
MC 300 - Hopper fed




Built-in oil cooler.





View of motor of the MC 300 - Hopper fed.

Heavy Duty Emulsifiers

MC 250 & MC 300 - SCREW HOPPER FED



MC 300 - Screw hopper fed



View of hopper infeed of MC 300 - Screw hopper fed

Heavy Duty Emulsifiers

MC 250 & MC 300 - PUMP FED

The industry “Work Horse” – scansteel foodtech® emulsifier does it all!

The scansteel foodtech® MC 250 & MC 300 emulsifiers have a unique dual feeding/two steps feeding system:

- Stand-alone feeding pump, feeding the lining/housing of the MC 250 & MC 300.
- Feeding/crushing screw, feeding the knife set.


The feeding pump with its own feeding screw with block breaking/bone breaking capabilities force-feeds the scansteel foodtech® MC 250 & MC 300 emulsifier lining/housing. Entering the lining/housing, the feeding screw of the MC 250 & MC 300 further force-feeds/grinds any particles, being frozen meat raw materials and/or bones. The feeding screw with its recessed 3-bladed knife distributes any products continuously towards the first hole plate securing optimal cutting/emulsifying effect.




Top view of pump infeed section showing the worm/ auger of MC 250.

Inline defrosting:

Heavy Duty steam valves connected directly in-line in the lining/feeding screw to secure even distribution of steam and subsequently final temperature.




Close-up Heavy Duty steam valves with and without cover.



Heavy Duty Emulsifiers

MC 250 & MC 300 - PUMP FED



Built-in oil coolers for gear box dramatically increase life time of the gear box.

Designed to Emulsify/ Particle Reduce Products Such as, Examples Only:

- Pre-broken, frozen meat raw material.
- Fresh meat raw material.
- Chicken bones, pork bones, beef bones.
- Frozen and fresh combination of above.

Knife Set:

The scansteel foodtech[®] MC 250 & MC 300 emulsifiers can be equipped with single, double, or triple knife set.

Controllable emulsifying effect with more/less hole plates:

1 hole plate = 1 (one) cutting edge against hole plate.

2 hole plates = 3 (three) cutting edges against hole plates.

3 hole plates = 5 (five) cutting edges against hole plates.

With the wide selection of knives and hole plates, the scansteel foodtech[®] MC 250 & MC 300 emulsifiers ensure you get the final emulsion/final product quality you require.




Technical Specifications	Model MC 250	Model MC 300
Capacity (approx.)	4000 – 12,000 kg/hour	6000 – 18,000 kg/hour
Power motor	90-200 kW	90-200 kW
Lenght	2300 mm	2300 mm
Width	1000 mm	1000 mm
Height	1700 mm	1700 mm
Weight	1500 kg	2000 kg

Pre-emulsifiers

PE 400 & PE 550



Pre-emulsifier PE 400



Meat-Bone Separators

SCANDEBONE 100 & SCANDEBONE 150 - PUMP FEED SYSTEM

scansteel foodtech® scanDebone 100 & scanDebone 150 are high-quality mechanical deboning machines for meat-bone separation for the poultry and processing industries. scanDebone 100 & scanDebone 150 are designed in such a way that the final product temperature increase has been minimized throughout the entire operation.



The scansteel foodtech® scanDebone series produces an adjustable, very high yield and at the same time it produces a final product with low calcium content in the final poultry and fish raw materials, which supports a high product quality.



Superpump SP 250 shown below feeding a scanDebone 150.



scanDebone 150 shown without slit filter.




scanDebone mounted with slit filters.



Slit filter seen from inside.



Final product: deboned poultry. View 1 (one).



Final product: deboned poultry. View 2 (two).

Gravy Production Systems

SCANGRAVY

The scansteel foodtech® scanGravy mixing and storage series has been designed to manufacture a wide range of pet food gravies, from light weight gravies to heavy viscous gravies. The scanGravy mixing and storage units are manufactured from 500 L – 6000 L. One entire system is controlled and operated by its own dedicated PLC system with optional software.



Pumps are positioned/mounted on their own frame for easy access at inspection/maintenance, etc. In addition, the pump of the scanGravy mixing unit can be equipped with its own knife system for eliminating lumps in "challenging to produce" gravies.

Mixing container designed for heavy viscous gravies/ mixtures. The Ytron and the Venturi system in combination with the Heavy Duty mixing agitators ensure a fast processing of a gravy free from lumps. Anti-vortex breakers are standard in all scanGravy mixing tanks. Direct steam injection for temperature control can be added as well.

Gravy Production Systems

scansteel foodtech® scanGravy with Ytron Powder Dispenser - Heavy Duty Applications



The mixing tank is used to dissolve or disperse powdered products in a liquid or to mix different liquids, with the Ytron powder dispenser for dissolving all dry "challenging to add" matters/ingredients in the gravy and/or the brine.

The Ytron in combination with the scanGravy secures complete dissolving of all dry matters, each particle is enclosed by water, ensuring that no "clumps" will occur. At the same time, use of ingredients can be minimized.

The liquid is circulated by a centrifugal pump, after which the hopper is loaded with ingredients such as salt, phosphate, soy protein, starch, and/or spices.

When the Gravy solution is fully dispersed, it can be pumped directly to a scanGravy storage tank. Dry matter inlet hopper: Approx. 15 l.

scansteel foodtech® scanGravy with Venturi System



scansteel foodtech® high speed dry ingredients addition Venturi system. For addition of all kinds of dry ingredients. Prevents air injection into gravy during production of same.





Storage & Batching Systems

SILO SYSTEMS

Over the years, scansteel foodtech A/S has gained substantial experience within both manual batching (swing loaders) and weighing equipment as well as automated batching and weighing (silo) systems.

Silo Systems:

Each silo typically from 2000 - 10,000 litres. Each silo is capable of storing pre-ground, frozen meat raw material as well as fresh meat raw material. Each silo is typically equipped with a stirring device/wing to prevent pre-ground meat raw material from freezing together, and is typically equipped with weighing-/load cells to accurately control the batch weight just as the weighing-/load cells are used to accurately weigh out the exact amount(s) according to the recipes. The scansteel foodtech® silos are typically equipped with a discharge screw which handles both pre-ground, frozen- and fresh meat raw materials.




View of standard bolt system and safety bolt system.

View of the inside of silos.

Storage & Batching Systems

FULLY AUTOMATIC SILO SYSTEMS



scansteel foodtech 10 unit silo system with 3000 liter silos. Showing both horizontal infeed screw for feeding the silos as well as discharge screw showing how the batching and discharge of the silo system. Typically, each scansteel foodtech silo is equipped with load-/weighing cells and as such the silos can discharge simultaneously in order to create pet food recipes fastest possible, and without delay. It is also shown that the large discharge- and batching screw can easily be pulled out for inspection and maintenance.



View of the silo discharge screw bearing with and without safety cover.

View of the silo discharge screw of the silos showcasing the easy access for cleaning and inspection without hidden surfaces.



Storage & Batching Systems

SWING LOADER WITH WEIGHING BELT

This is a line consisting of typically 3-10 swing loaders which require 1 (one) person (operator) only. One person (operator) can semi-automatically/semi-automatically weigh out between 2-6 batches per hour and as such, the same person (operator) can quite easily feed a continuous processing line with two or more mixers.



6 (six) unit weighing station, seen from the infeed side. Typically, Dolav bins are fed into the swing loaders by a fork lift truck. All is controllable from the operator panel.



6 (six) unit weighing station, seen from the batching/weighing side. The operator looks at the control panel to the right to check how many kilos he requires of a certain meat raw material. Next, the operator looks at the operator panels in front of each swing loader to see where he has to unload/weigh out the volume of the meat required. The weighing belt is equipped with 4 (four) load cells in order to monitor weights continuously.

Storage & Batching Systems

SWING LOADER WITH WEIGHT INDICATOR



Overview of the entire weighing and batching station, seen from the batching/weighing side.



Control panel for operator instructions in terms of next meat raw material to weigh out.



Details showing drip trays and weighing/load cells.



Line control of weighing and batching station.

Storage & Batching Systems

scansteel foodtech A/S has a wide range of different standard solutions for both weighing and batching applications. In addition, we do design and manufacture tailor-made systems according to customers' requirements and demands.



Belt conveyors with a range of standardized side rails and drip pans to avoid moisture and liquids on the floor.



All scansteel foodtech[®] belt conveyors can be equipped with weighing cells/ system for exact batching.



One option in the scansteel foodtech[®] "batching family of solutions" is a station of typically 2 – 8 swing loaders (tippers) which can hold different meat raw material.



With the scansteel foodtech[®] line control, it is possible to guide the operator into the exact amount of each meat raw material to be unloaded onto the weighing/batching belt conveyor.

INFEEED SYSTEMS FOR GRINDERS - FROZEN BLOCKS - BELT CONVEYORS

scansteel foodtech A/S manufactures a wide range of belt conveyors. Except for a range of standard belt conveyors, scansteel foodtech A/S designs belt conveyors according to customer requests and requirements. All frames are manufactured in stainless steel, and belt types can vary to customer request and requirements. The scansteel foodtech[®] belt conveyors are driven by either drum motors or gear box motors, again according to customer requirements. In addition, belt conveyors can be equipped with metal detectors and/or blue plastic detectors.



Example of scansteel foodtech[®] infeed systems shown with belt conveyor, unpacking station and CombiGrind CG 300 HD



Belt Conveyor with unpacking station with 2 (two) lifting tables for ergonomics, left side.



Belt Conveyor with Unpacking station with 2 (two) lifting tables for ergonomics, right side.

Product Transfer Equipment

INFEED SYSTEMS FOR GRINDERS - FROZEN BLOCKS - BELT CONVEYORS

Standard scansteel foodtech® inclined belt conveyor with metal detector for feeding a grinder. Shown with unpacking table with weighing/load cells for batching purposes.





Standard scansteel foodtech® inclined belt conveyor with metal detector, side view. scansteel foodtech A/S can deliver our belt conveyors with any brand type metal detector. Side view.



Standard scansteel foodtech® inclined belt conveyor with metal detector, Front top view. scansteel foodtech A/S can deliver our belt conveyors with any brand type metal detector. Front top view.

INFEED SYSTEMS FOR GRINDERS - INCLINED CHAIN BULK CONVEYOR



The scansteel foodtech® Inclined Chain Bulk Conveyor is designed with a pitch chain system in each side of the bulk conveyor and equipped with stainless steel guides/flights for transportation of the product. The Inclined Chain Bulk Conveyor can be equipped with infeed chute if used in combination with other belt conveyor installations.

Product Transfer Equipment

scansteel®
foodtech

INFEED SYSTEMS FOR GRINDERS - FRESH MEAT RAW MATERIAL - BELT CONVEYORS

Example of a scansteel foodtech® solution feeding fresh meat raw materials into a grinder with continuous metal detection. Fresh meat raw material is fed onto the belt conveyor via a scansteel foodtech scanSwing loader. This solution can also be supplied with a combined solution of both fresh- and frozen meat raw materials.




Top view of scanSwing loader and belt conveyor

Product Transfer Equipment

INFEED SYSTEMS FOR GRINDERS - BELT CONVEYORS

scansteel foodtech® inclined belt conveyor with metal detector, for feeding of frozen blocks, and automatic reject of frozen blocks being detected with metal pieces.



scansteel foodtech® inclined belt conveyor with metal detector.




Inclined belt conveyor with side racks.




Inclined chain conveyor for frozen blocks.

DISCHARGE SOLUTION FOR GRINDERS - HORIZONTAL BELT CONVEYORS



Another typical horizontal belt conveyor solution where 2 (two) grinders are discharging onto the scansteel foodtech[®] belt conveyor. This solution saves a lot of safety devices and, at the same time, secures easy access to the grinders for cleaning, mounting, and dismounting of the grinders, front view.



Another typical horizontal belt conveyor solution where two grinders are discharging onto the scansteel foodtech[®] belt conveyor. This solution saves a lot of safety devices and, at the same time, secures easy access to the grinders for cleaning, mounting and dismounting of the grinders, top view where the transfer point from grinders to belt conveyor is clearly seen.




All scansteel foodtech[®] belt conveyors can upon customers request be manufactured with drip trays/ collection pans in order to avoid moisture on the floor.

Product Transfer Equipment


DISCHARGE SOLUTION FOR GRINDERS / FEEDING OF MIXERS -SCREW CONVEYOR & BELT CONVEYOR SOLUTIONS

scansteel foodtech A/S supplies various solutions where screw- and belt conveyors are combined. A typical solution might be discharging from one or two grinders into two or more mixers.




Close-up view showing scansteel foodtech® inclined screw conveyor feeding onto a scansteel foodtech® horizontal belt conveyor which has 3 (three) main positions.

This position shows the belt conveyor feeding a scansteel foodtech® mixer on left hand side.



Close-up view showing scansteel foodtech® inclined screw conveyor feeding onto a scansteel foodtech® horizontal belt conveyor which has 3 (three) main positions.

This position shows the belt conveyor in neutral position in order for both mixer lids to be capable of closing.




Close-up view showing scansteel foodtech® inclined screw conveyor feeding onto a scansteel foodtech® horizontal belt conveyor which has 3 (three) main positions.

This position shows the belt conveyor feeding a scansteel foodtech® mixer on right hand side.


Product Transfer Equipment

SCREW CONVEYORS Ø240 - Ø600 MM **- INCLINED, HORIZONTAL, AND VERTICAL SCREW CONVEYORS**

From 1500 - 10,000 mm in length. scansteel foodtech A/S has a full range of standard designed screw conveyors. In addition, 100% tailor-made screw conveyors, designed according to customer request, are also available. As optional extras, the scansteel foodtech® range of screw conveyors can be supplied with or without hydraulic lifting and lowering systems.



Example of infeed section for grinder.



Heavy Duty shaft bearings shown.



Standard screw conveyor electrical/operator panel.



Please also note built-in drain plug for draining/cleaning purposes.

Product Transfer Equipment

scansteel®
foodtech

SCREW CONVEYORS Ø240 - Ø600 MM

- INCLINED, HORIZONTAL, AND VERTICAL SCREW CONVEYORS



Inclined screw conveyor with hydraulic knockdown system for cleaning, inspection, and maintenance purposes.



Mirror polished screw.



Optional: Safety grill for safety lid.

(While cleaning and the screw is running)



Screw conveyor in knock down position ready for inspection and/or cleaning.

Product Transfer Equipment

scansteel®
foodtech

SCANGIRAFF WITH SILO/BUFFER

Example of scansteel foodtech® scanGiraff with buffer silo with stirring/feeding device to prevent bridge building.



scansteel foodtech® standard scanGiraff, showing vertical screw.



Top view of scansteel foodtech® standard scanGiraff, showing stirring/feeding device.

Product Transfer Equipment

scansteel®
foodtech

SCANGIRAFF Ø240 MM



scansteel foodtech® standard scanGiraff for positioning under a grinder and/or a flaker.



scansteel foodtech® standard scanGiraff shown in cleaning position. Note the vertical screw is 100% accessible for cleaning (no hidden zones).



Large diameter infeed screw in horizontal infeed hopper.

Product Transfer Equipment

scansteel®
foodtech

SCANGIRAFF Ø470 MM FOR HEAVY DUTY APPLICATIONS



scanGiraff shown in closed position, ready for production.



scanGiraff shown in cleaning and inspection position.



Infeed hopper shown with safety guard/grill in running position.



Infeed hopper shown with safety guard/grill in cleaning and inspection position.

SCANLIFT SINGLE COLUMN

- FULL RANGE OF STANDARD LIFTING DEVICES FOR 200 - 300 L TROLLEYS



scanLift SC 350
shown with 220 L trolley.




scanLift SC 350
shown with 300 L trolley.



scanLift SC 350 with 220 L trolley shown in
discharge position. Equipped with discharge
chute/non-spill chute.



scanLift SC 350 electrical/operator panel.



Type A and B Discharge Height in mm.	Type C and D Discharge Height in mm.
1400 – 1700	1400 – 1700
1700 – 2000	1700 – 2000
2000 – 2300	2000 – 2300
2300 – 2600	2300 – 2600
2600 – 2900	2600 – 2900
2900 – 3200	2900 – 3200
3200 – 3500	3200 – 3500
3500 – 3800	3500 – 3800
3800 – 4100	3800 – 4100

Product Transfer Equipment

scansteel[®]
foodtech

SCANLIFT SINGLE COLUMN

- FULL RANGE OF STANDARD LIFTING DEVICES FOR 200 - 300 L TROLLEYS



i Please contact us

Please contact scansteel foodtech A/S for special application/lifting devices for boxes, trolleys, and Dolav boxes.

*scanLift SC 350
shown with safety cage.*

*Special application
kettle/bowl.*



Product Transfer Equipment

scansteel®
foodtech

SCANLIFT DOUBLE COLUMN

- ALL TYPES OF 220 - 300 L TROLLEYS AND BOXES/DOLAV BOXES

Double column lifting device
for plastic/metal crates/boxes.
– Dual function, shown with
plastic crates/boxes.



Double column lifting device
for plastic/metal crates/boxes.
– Dual function, shown with
200/300 L trolley.



Detail showing how forks
for 200/300 L trolley work
combined with plastic/metal
crates and boxes.


SCANLIFT DOUBLE COLUMN LOADER WITH PALLET INVERTER

This is the ultimate Heavy Duty Double Column Loader with built in hydraulic pallet inverter, scanLift has been designed for lifting/feeding of whole pallets of frozen blocks, containers of frozen blocks and similar applications. A typical application is feeding into the scansteel foodtech® whole Pallet Crusher, WPC series. The built in pallet inverter eliminates the need for a stand alone pallet inverter (depending on exact and specific application and customer needs/demand).



The scanLift Double Column loader with pallet inverter shown with all safety fences is running position.

The scanLift Double Column loader with pallet inverter shown in infeed position with safety gate open. Also the pallet inverter is shown. Typically the double column loader is loaded with a fork lift truck.



Product Transfer Equipment

scansteel[®]
foodtech

SCANSWING LOADER

- scansteel foodtech A/S HAS A FULL RANGE OF SWING LOADERS

*scansteel foodtech®
scanSwing
loader in down
position.*

*scanSwing loader
in empty position.*




*scanSwing loader shown with bone
product.*



*Machine feet which can be mounted
to the floor.*






*Operator/control panel with emergency
stop.*




Inside view of hydraulic system.

scansteel®
foodtech




Layout


STANDARD LINE 1 AND STANDARD LINE 1, PLUS




STANDARD LINE 2



STANDARD LINE 3



STANDARD LINE 4




scansteel®
foodtech

26 AGENTS & DISTRIBUTORS

SPREAD OVER 6 CONTINENTS

ACTIVE IN 56 COUNTRIES




Find your local
scansteel foodtech contact



scansteel foodtech headquarters Site 1 - 10,450 m²



scansteel foodtech Site 2 - 1300 m² manufacturing



April 2025 Edition

Follow us on Social Media



scansteel foodtech



scansteel foodtech A/S



scansteel foodtech

scansteel foodtech A/S

Industrivej 6
4200 Slagelse
Denmark

Phone: +45 7027 1410

Fax: +45 7027 1411

www.scansteelfoodtech.com